

Span/load tables

Trimapanel, 120 mm core

Feb-15

The span tables below have been created in accordance with EN 14509. For the use of wall cladding only

The values are based on a maximum permitted deflection of span/150

Fastener performance has been taken into account within these tables, this is based on a 2mm thick steel rail and assumes 2 fasteners at each end support and 2 fasteners at each intermediate support

The panel is assumed to have a minimal land of 60 mm at each support position

Safe Imposed (positive) Loads (kN/m²)

Span (m)	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00
Single span	12.39	8.26	6.20	4.96	3.86	2.96	2.31	1.83	1.47	1.19	0.98
Double span	12.40	8.27	6.20	4.96	4.14	3.20	2.45	1.79	1.36	1.07	0.87
Multi span	12.40	8.27	6.20	4.96	4.13	3.20	2.45	1.93	1.57	1.27	1.05

Safe Wind Suction (negative) Loads (kN/m²)

Span (m)	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00
Single span	-8.43	-5.62	-4.22	-3.37	-2.79	-2.05	-1.57	-1.24	-1.01	-0.83	-0.70
Double span	-4.22	-2.81	-2.11	-1.69	-1.41	-1.20	-1.05	-0.94	-0.84	-0.77	-0.70
Multi span	-4.22	-2.81	-2.11	-1.69	-1.41	-1.20	-1.05	-0.94	-0.84	-0.77	-0.70

While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel Europe Limited, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading.

Building Systems UK

Shotton Works • Deeside • Flintshire • CH5 2NH • UK

T: +44 (0) 1244 892199 • F: +44 (0) 1244 892121 • www.tatasteelconstruction.com/theworks

Tata Steel UK Limited • 30 Millbank • London SW1P 4WY • Registered in England No. 2280000